

## BATHROOM DIVA IP44 LED OVER MIRROR LIGHTS

# ROBUS®

This attractive looking over-mirror light is available in a choice of lengths, wattages and light outputs and is equally suitable for use in domestic or entertainment venue bathrooms, or professional cloak or makeup rooms.



### Applications:

- Domestic bathrooms
- Cloakrooms in venues such as:
  - Pubs
  - Clubs
  - Wine bars
  - Restaurants
  - Cinemas
  - Theatres

### Construction:

Extruded aluminium body  
Opal polycarbonate diffuser  
ABS chrome end caps

### Features:

- Available in 600mm long 15 Watt and 900mm long 20 Watt power options
- Lumen packages of 1200lm or 1600lm
- Extruded aluminium main body
- Polycarbonate diffuser
- Polished chrome end caps
- End cap mounted on/off switch
- Ingress protection rating of IP44
- Light colour temperature of 3000K with high colour rendering index of >80
- Operating temperature of -20° C to +40° C
- Can be operated 24/7
- Removable large rubber plug provides access to termination area containing electrical connector
- Class 2 fitting
- Recessed channel in aluminium body profile
- Mounting kit included


### Benefits:

- Ideal for small or larger mirrors accommodating widths up to 2metres
- Replaces >60W traditional Incandescent making savings of 75% and providing efficacies of >80 lm/cctW
- Over twice the light output of traditional incandescent
- Generous complimentary lighting for large or smaller bathrooms
- Provides good thermal management to keep LED's operating at optimum temperature for long life
- Allows maximum light transmission with reduced glare
- Looks attractive and adds a touch of class
- Allows local switching in addition to being switched with main lighting
- Suitable for use in Bathrooms Zone 2 (Where it may get splashed)
- Warm white, high quality light to reproduce true colours of skin tones or attire
- Provides for operation in a wide range of ambient temperatures
- Ideal for bathrooms in theatres, cinemas or other venues where cloakrooms are in constant use
- Easy access allows quick and simple electrical connection
- Up to 2.5mm<sup>2</sup> CSA solid conductors may be terminated
- Simple installation – no earth required
- Provides route for cable to run if not directly in line with connector
- Body of fitting push fits over wall mounted brackets for fast and simple installation

BATHROOM  
DIVA IP44 LED OVER MIRROR LIGHTS

**ROBUS**<sup>®</sup>

Product Code:	RDA1530-03	RDA2030-03
Comparable to Halogen (W):	60	60
Total Power (W):	15	20
Total Light Output (lm):	1,200	1,600
Efficacy (lm / cctW):	80	80
Rated Life (hrs):	30,000	30,000
Warranty (yrs):	3	3
Illuminance at 1m (lux):	350	430
Beam Angle (deg):	130	130
CCT (K):	3,000	3,000
CRI (Ra):	80	80
Ingress Protection (IP):	44	44
Operating Temperature (°C):	-20 < Ta < +40	-20 < Ta < +40
Operating Voltage (Vac):	220 - 240	220-240
Power Factor (PF):	0.5	0.5
Length (mm):	600	900
Width (mm):	53	53
Depth (mm):	65	65
Box Qty:	1	1
Weight (kg):	0.5	0.93



Cone Illuminance Diagram:




Diagram for RDA1530-15. Other diagrams available on request

Standards & Approvals:

Complies with: EN 55051, EN 61000-3-2, EN 61000-3-3, EN 61547, EN 60598-2-1, IEC 62778, EN 62493



Polar Intensity Diagram:




Diagram for RDA1530-15. Other diagrams available on request



PLEASE NOTE: INFORMATION IN THIS DOCUMENT MAY BE SUBJECT TO CHANGE WITHOUT PRIOR NOTICE

IRE: TEL: +353 1 709 9000 WEB: WWW.LEDGROUPROBUS.COM  
AUS: TEL: +61 7 3890 5444 WEB: WWW.LEDGROUPROBUS.COM.AU