## ROBUS®

## QUALITY PRODUCTS BY LED GROUP

## OUTDOOR

## **ECLIPSE IP54 LED WALL LIGHT**

	Codes:	REL0630-25	REL1230-25
	Comparable to CFL(W):	11	18
	Light Output L <sub>100</sub> (Im):	370	720
	Beam Angle (deg):	120	120
	Illuminance @ 1m (lx):	35	60
W	Colour Temp L100 (k):	3,000	3,000
	CRI L100 (Ra):	80	80
	Total Power Consumed (W):	6	12
• H	Efficacy (Im/cctW):	60	60
	Power Factor:	0.8	0.8
	Rated LED life (hrs):	30,000	30,000
	Ingress Protection (IP):	54	54
Height Width Depth	Ambient Operating Temp (°C):	-20 <ta<+40< th=""><th>-20<ta<+40< th=""></ta<+40<></th></ta<+40<>	-20 <ta<+40< th=""></ta<+40<>
REL0630 86 160 100	Operating voltage (V):	100-240	100-240
	Min Order Qty/Carton Qty:	1/12	1/8
REL1230 129 249 149	Weight (Kg):	0.58	1.1
	Warranty (yrs):	3	3

This superb looking fitting is manufactured from traditional high quality die cast aluminium with polycarbonate diffuser. It utilises state of the art LED technology to provide a great light output from a choice of wattages. It offers an attractive outdoor lighting solution with very low running costs and without the annoying failures associated with traditional light source lamps.

Surface mounted either as an up lighter or down lighter, these fittings are typically installed in domestic applications but can equally be used to excellent effect in sheltered housing outdoor common areas, hotel and restaurant or pub walkway applications without worry of burning if touched by children.

FEATURES	BENEFITS
<ul> <li>Modern design</li> <li>Body manufactured from die cast aluminium with allen head type wall plate retaining machine screws</li> <li>Finished with a dark grey electrophoresis powder coating</li> </ul>	<ul> <li>Great aesthetics with an individual look. Can be used for up or down lighter applications</li> <li>Strong and durable</li> <li>Exudes high quality and will not rust</li> <li>Long lasting finish which will look good for many years</li> </ul>
Opal polycarbonate diffuser	<ul> <li>Provides a soft light with reduced glare</li> <li>Uniform light spread</li> </ul>
Ingress protection to IP54	<ul> <li>Ideal for installation outdoors</li> <li>Ensures water or dust cannot enter the fitting so provides long life</li> </ul>
Twin screw mounting wall plate	• Provides fast and simple mounting and access for electrical connection
<ul> <li>Utilises high quality Runlite LED's to provide:</li> <li>High luminous flux</li> <li>Low power consumption</li> <li>High efficacy</li> <li>Long LED life</li> </ul>	<ul> <li>Compared to traditional CFL &amp; Incandescent light sources:</li> <li>Comparable light output</li> <li>Provides energy savings of over 40%</li> <li>Complies with Building Regulation efficacy requirement</li> <li>Last up to 20 times longer so no annoying lamp changes</li> </ul>
High quality, high CRI warm white light	<ul> <li>Provides a warm subtle lighting ambience</li> <li>Good quality light is always available for peace of mind and security</li> </ul>
Integral driver	No separate enclosure required for power supply
No Infra-red or Ultra-violet in the light beam	• Is cool to touch so will not burn if touched
Robus 3 year warranty	<ul> <li>No internet registration or forms to fill in</li> <li>A quality energy efficient long life product</li> <li>Fit and forget - peace of mind</li> </ul>

PLEASE NOTE - INFORMATION CONTAINED IN THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE



Western Retail Park Nangor Road Dublin 12 **Tel** +353 1 709 9000 Fax +353 1 709 9060 Email info@ledgrouprobus.com www.ledgrouprobus.com

www.robusdirect.com

Ireland