

LED STRIP 168LED/M • 24V • 17W • 3000K • IP68 • 2200LM • RA80 • 10MM




12W /m
 24V DC
 140 lm/W LM80 SDCM ≤ 3
 6.25cm cutting length
 3oz 8mm FPC
 Ra>80, available over 95
 75000h L70 lifespan
 30m reel for IP20, 10m for IP66 / IP68
 Warranty 3 years

High quality LED strip for professional use with seven LEDs in one module to achieve luminous efficacy up to 140 lm/W. Two layers of PCB with 3oz copper paths characterized by a lower voltage drop and lower operating temperature. On a base using adhesive tape 3M 300 LSE. LEDs that meet requirements of LM-80 test, guaranteeing small lumen decrease and colour constancy in time.

Specification

Parameter	Value	ETIM ID
Symbol	SPE-168-68-WW-24	
EAN13	5901289754484	
ETIM CLASS	Light ribbon-/hose/-strip	EC002706
Power [W]	17	EF008319
Voltage [V]	24	EF008856
cutting length [cm]	4.17	EF008320
Colour of light	White	EF009350
Model	Tape	EF000010
Number of nodes per meter	168	EF008340
Voltage type	DC	EF000187
Beam angle [°]	120	EF000128
Wskaźnik oddawania barw CRI	>80	EF000442
With Self-adhesive	tak	EF000434
Colour temperature [K]	3000	EF009346
Degree of protection	IP68	EF005474
Suitable for use		
Luminous flux [lm]	2200	EF010867
Min. number of switching cycles	50000	EF012201
Rated life time L70/B50 at 25 °C [h]	50000	EF011870
Width [mm]	10	EF000008
Height/depth [mm]	4.4	EF001456
Energy efficiency class of the built-in lamp	A++, A+, A (LED)	EF012487

Dimensions



	IP20	8.0 x 1.4 mm
	IP66	8.3 x 1.7 mm
	IP68	10.0 x 4.4 mm