

LED STRIP 120LED/M 1M • 24V • 19.2W • 2700K - 6000K • IP20 • 1930LM • RA80 • 8MM



19.2W /m
24V DC
100lm/W
5cm cutting length
3oz 10mm FPC
Ra>80
50000h L70 lifespan
30m reel for IP20, 10m for IP66
Warranty 3 years

High quality LED strip for professional use with luminous efficacy 100lm/W. LEDs with double chip warm white (2700K) and cool white (6000K) allows to adjust the colour temperature according to your needs. Two layers of PCB 10mm width, with 3oz copper paths characterized by a lower voltage drop and lower operating temperature. On a base using adhesive tape 3M 300 LSE.

Specification

Parameter	Value	ETIM ID
Symbol	SPA-120-CCT-24	
EAN13	5901289753357	
ETIM CLASS	Light ribbon-/hose/-strip	EC002706
Power [W]	19.2	EF008319
Voltage [V]	24	EF008856
cutting length [cm]	5	EF008320
Colour of light	White	EF009350
Model	Tape	EF000010
Number of nodes per meter	120	EF008340
Voltage type	DC	EF000187
Beam angle [°]	120	EF000128
Wskaźnik oddawania barw CRI	>80	EF000442
With Self-adhesive	tak	EF000434
Colour temperature [K]	2700 - 6000	EF009346
Degree of protection	IP20	EF005474
Suitable for use		
Luminous flux [lm]	1930	EF010867
Min. number of switching cycles	50000	EF012201
Rated life time L70/B50 at 25 °C [h]	50000	EF011870
Width [mm]	10	EF000008
Height/depth [mm]	2	EF001456
Energy efficiency class of the built-in lamp	A++, A+, A (LED)	EF012487

Dimensions

