

LED STRIP 240LED/M 1M • 24V • 24W • 4000K • IP20 • 2600LM • RA80 • 10MM



24W /m
24V DC
120lm/W LM80 SDCM ≤ 3
2.5cm cutting length
3oz 10mm FPC
Ra>80, available over 95
75000h L70 lifespan
30m reel for IP20, 10m for IP66
Warranty 3 years

High quality LED strip for professional use with luminous efficacy 120lm/W. Two layers of PCB with 3oz copper paths characterized by a lower voltage drop and lower operating temperature. On a base using adhesive tape 3M 300 LSE. LEDs that meet requirements of LM-80 test, guaranteeing small lumen decrease and colour constancy in time.

Specification

Parameter	Value	ETIM ID
Symbol	SCA-240-NW-24	
EAN13	5901289753937	
ETIM CLASS	Light ribbon-/hose/-strip	EC002706
Power [W]	24	EF008319
Voltage [V]	24	EF008856
cutting length [cm]	2.5	EF008320
Colour of light	White	EF009350
Model	Tape	EF000010
Number of nodes per meter	240	EF008340
Voltage type	DC	EF000187
Beam angle [°]	120	EF000128
Wskaźnik oddawania barw CRI	>80	EF000442
With Self-adhesive	tak	EF000434
Min. number of switching cycles	50000	EF012201
Rated life time L70/B50 at 25 °C [h]	75000	EF011870
Width [mm]	12	EF000008
Height/depth [mm]	4.4	EF001456
Colour temperature [K]	4000	EF009346
Degree of protection	IP20	EF005474
Suitable for use		
Luminous flux [lm]	2600	EF010867
Energy efficiency class of the built-in lamp	A++, A+, A (LED)	EF012487

Dimensions

